

2017 All Stars Hobby Stock Rules

RaceCeivers mandatory. This is a POST RACE TECH ITEM

DEFINITION OF “STOCK” OR “OEM”

In the following rules stock, stock OEM or OEM will mean that a part or dimension must be from a standard production vehicle. “OEM” is the abbreviation for original equipment manufacturer. If parts are to be stock, stock OEM or OEM then they can not be GM Performance, Bow-tie, Ford Motorsports, SVO, Direct Connection such as Performance Catalogs, Marine, Mail Order or any special Off-Road or Racing Performance Parts. No carbon fiber parts anywhere on the car. Absolutely no removal, alteration or covering of casting numbers, manufacturer’s name, logos, insignias, etc. from any item on the car. To do so will make that part illegal and it will be treated as such.

MODELS:

1. Open to 6 or 8 cylinder rear wheel drive passenger automobiles with a minimum wheelbase of 100 inches. Station wagons or pick-ups are allowed. This is a passenger optional class

BODIES:

1. Must be manufacturers stock for year model used. Fenders, doors and rear quarter panels may be interchanged with similar models as long as end result looks stock and does not effect the size or weight of vehicle. Any fabricated body part must be 22-gauge steel or aluminum and appear stock as per track official. **Stock Steel roofs only.** Stock appearing bodies will be strictly enforced.

2. Interior sheet metal may be removed. The dash and package tray may be replaced with sheet metal. **No enclosed driver compartment, no interior sheet metal, subject to technical inspection.**

3. No cutting away of exterior sheet metal except as outlined:

a.) Body sheet metal may be trimmed for tire clearance a maximum of 5” above tire on both sides of car in race ready position.

b.) Rear trunk floor and outer portion of inner fender panels may be removed.

c.) All glass and chrome trim must be removed. No other alterations except to install roll cage.

d.) **All body parts must look stock as per track officials. No sail panels of any kind. Must have opening for rear side window and cannot be covered with any kind of material. No exceptions.**

4. The hood must be complete and stock. The air cleaner must remain completely under hood. Hood and deck lid must have approved quick pull positive hold pins. Rear deck lids (trunk) must slope downward towards the rear of the car as per track officials. Hood scoop legal as long as completely enclosed.

5. No fiberglass or plastic fenders, hoods, trunk lids or quarter panels may be utilized.

6. Engine to driver’s compartment must be completely sealed. Driver to trunk area must be completely sealed.

7. No spoilers front or rear allowed. No body side skirts allowed.

8. Complete stock floor pan mandatory. Must run full stock interior floor pan, turn up to turn up. Stock firewall, master cylinder stock location. Pedal assemblies in stock location.
9. No glass windshields allowed. The complete windshield area must be covered with wire mesh with minimum ¼" openings or maximum of 1" openings. Must have center support.
10. Number must be on both sides of car located on door. Must also have number located on roof and on front of car located in approximate headlight area and taillight area. Minimum number size is 20". Number lines must be a minimum of 4" and in contrasting color to the body of car.
11. Driver-side window net required, minimum 16 inch by 20 inch ribbon or mesh style, and must be mounted to roll cage so latch is at top front of window. Strict enforcement on secure mounting. No zip ties or pop riveting. Hard mount only.
12. No mirrors of any kind allowed.
13. No radios allowed.
14. Appearance of car must be kept up to track standards. This will be strictly enforced.

ENGINE:

Engines will be teched and will have 16 in./lbs. of vacuum at 600 RPM.

1. **ENGINE BLOCKS:** Stock OEM engine blocks only. No aluminum. 360 cubic inch max. Decking allowed. Studded main caps allowed. Must have stock casting numbers on block. Blocks must not be altered in any way so that it could not be used in a street legal production car.
2. **CRANKS:** Stock OEM cast, large journal, 3.48 stroke crank or Scat series 9000 stock replacement allowed. This is a no touch crank. No knifing, no lightening. No offset grinding. No stroking. No destrokking. No steel cranks allowed. No lightweight cranks allowed. Crank is to remain stock and will be teched.
3. **PISTONS:** Stock OEM piston allowed. Any flat top piston allowed. No lightening of any kind. No domed pistons allowed. Pistons are no touch.
4. **RODS:** Stock OEM 5.7, or Scat 5.7 stock replacement, large journal rod allowed. No 6" rods allowed. No aluminum, no lighting of any kind. Floater rod pins OK. No cap screws, thru bolt w/ nuts only. Heavy rod bolts OK. Shot peened OK. No polishing. No after market rod allowed. Rods are no touch.
5. **HEADS:** Stock OEM 1.94 intake (max.) 1.6 exhaust (max.) allowed. No vortex, no fuel injection or aluminum allowed. No performance after market heads allowed. No port matching, no pocket porting or blending. No angle plug heads. Stock appearing stamped steel rockers only. No alloy, roller tip or chrome moly allowed. No rollers. Screw in studs OK. Large valve springs OK. Guide plates OK. No titanium. World and Dart brand stock replacement heads are OK.
6. **CAMSHAFT:** .465 lift (max.) intake and exhaust. No roller cams. No solid lift cams. Any hydraulic lifters allowed. No gear drives allowed.
7. **INTAKE & CARB:** Stock cast iron 2 barrel or 4 barrel intake manifold or Torker II with an adapter to take the Holley #4412 carb. This is a no touch intake rule. No modification of any kind allowed. No restrictor plate required. Carburetor spacer must not exceed 1" max. No funneling of spacers. One Holley #4412 carb allowed. This is a no touch carb. You may remove choke plate and change the jetting.
8. Engine must be 9 to 1 compression only.

9. Exhaust pipes must extend to the rear of the driver and point to the outside of the car. Stock exhaust only. No high performance manifolds or headers allowed. No cast iron headers. No Brzezinski manifolds may be utilized. No modification of any kind allowed to exhaust manifolds. Mufflers mandatory. Maximum dB reading 95 decibels at 100 feet. Mufflers and tail pipes must be mounted below or underneath stock floor pan. No part of the exhaust system is allowed inside the driver's compartment.
10. Distributors must be stock point or HEI stock. No racing modules or coils allowed. No MSD or Mallory modules allowed. MSD or Mallory wires OK.
11. All cars must be equipped with one working starter mounted in stock location. Stock mini starters allowed. After market mini starters or gear starters allowed.
12. No electric fuel pumps allowed. Gasoline fuel only. No water mix fuel. Fuel cells mandatory. Fuel tank must be retained by minimum of four (4) straps; two (2) crossways, two (2) lengthwise.
13. Stock transmissions (automatic or standard) only. Automatic transmissions must be equipped with one stock working torque converter only, 11 inch diameter minimum width. No stall converter. Hydraulic clutch allowed. Clutch fluid reservoir must be a high mount.
14. All power steering pumps must be stock type for that year, make and model. After market pumps OK. Remote fluid cans are allowed.
15. No air forced boxes allowed.
16. Aluminum water pumps OK.
17. INSPECTION HOLE: Mandatory one inch inspection hole all pans , no obstruction to crank and rods. No gasket reimbursement will be provided if motor disassemble is required for inspection because of no inspection hole.
18. There must be a designated vacuum port on the intake manifold for tech inspection. After every main event, the top five finishers will go to the scales for a post race vacuum inspection. Failure to meet the vacuum requirement will cause disqualification. Failure to meet the requirement pre-race and the car will not be allowed to race.

ROLLBARS:

1. A full perimeter roll cage is required. No offset cage allowed. There must be a minimum of four (4) driver side bars in the left door area. Two (2) bars must extend from the top of roll cage to the rear of the frame rails. One (1) bar must extend from the left side to right side of rear roll cage at floor pan level for seat belt attachment. One (1) diagonal bar is required across the rear of roll cage from top to bottom. One (1) bar must be installed from left side of roll bar to center part of cross bar at shoulder level for shoulder harness attachment. Additional roll bars may be added. Where roll bars are attached to the floor pan, must have steel mounting plates under and over floor pan. Plates must be a minimum of 4" x 6" x .125 steel. Single pipe front loop may be installed at radiator top tank level. Radiator protection bar and supports may be added. Subject to technical inspection and approval. All radiator protection bars must be behind the bumper and under front nose piece. All main cage roll bar material must be a minimum of 1 3/4" .090" wall steel tubing or black iron pipe with a minimum of 1 1/4" ID schedule 40. No galvanized pipe. Maximum, pipe diameter 2". No thread pipe fittings allowed. All roll cage welds must have a minimum 2" x 11/2" x 11/2" x .125" steel gussets. All roll bar structure exposed to the driver must be padded with approved padding. Roll bar construction and installation is subject to inspection and approval. No offset roll cages. Speedway highly suggests 1/8" plates on left side door bars.
2. Racing seat mandatory. Seat must have complete cage frame support fabricated to the roll bar

assembly. No fiberglass seats.

3. A five (5) point safety harness, with quick release mandatory with a 3" wide lap belt, 3" shoulder belts and a 2" submarine. All belts must be attached to roll cage.
4. All seat belts must have date of manufacturer and must be within 3 years of the present date. It is for your safety.

FRAME AND SUSPENSION:

1. Frame must be stock only. No reinforcing or modifying allowed.
2. Wheel base Minimum allowable 108 inches. Wheelbase must match measurable wheelbase for car utilized +/- 1 inch.
3. Frames, front and rear sub frames must be stock for year, make and model of car utilized. No cutting, sectioning or redesign of any frame or sub frame to change the stock location of any suspension component or engine placement. Frame cannot be notched for fuel pump. Tubular rear clip additions made of box tubing allowed.
4. All components and parts must be stock. No reinforcing. No weight jack devices of any kind allowed. Front fixed spring buckets allowed. Fixed spring buckets allowed on rear of coil cars only. Racing springs allowed (AFCO and etc.).
5. No adjustable spring hangers allowed. Replacement hangers must be stock length for year, make and model of car utilized. No fabricated spring hangers. Sliders optional.
6. Fixed lowering blocks allowed.
7. Front sway bars must be stock, with stock connector links. No rear sway bars allowed. If a rear sway bar was on the car as part of the OEM, it must be removed.
8. Any crash damage repair must locate the suspension components in their original positions with a minimum of reinforcement. All repairs subject to Speedway inspection and approval. Front leaf spring mounts must be stock and in the stock location. Fabricated mounts are not allowed.
9. Stock "A" arms or tubular "A" arms are allowed. "A" arms may not be lengthened, shortened or modified in any way. "A" arm bushings must be stock type, no plastic or metal bushings allowed. Ball joint and ball joint location must be stock. "A" towers can not be moved.
10. No after market front spindles or brake rotors allowed. No modifications to spindles or rotors allowed.
11. All shocks must be stock type and must be mounted in stock location to stock mounts. No coil over, coil boosted, air shocks, adjustable and/or rebuildable shocks allowed.
12. Tube front and rear bumpers OK. Override and underride bars recommended. Must be turned back and capped and must fit under nose piece. Aluminum bumper O.K. Front and rear bumpers must be mounted at approximately stock height and location. Bumper height measured from ground to centerline of bumper must be a minimum of 16" and a maximum of 20". Bumpers must not be narrowed. Bumpers must have a 90-degree turn on each side extending back a minimum of 4" from front of car on front bumper. Must extend 4" forward from rear bumper. Bumpers must not have sharp corners or ends. Front and rear bumpers must have metal plates covering full width of bumper securing ends of bumpers to the quarter panels. Front and rear bumpers must have safety chains mounted to the frames. Bumpers are subject to tech approval, call for clarification. Bumpers cannot stick out passed bodies. No exceptions, it will be fixed.

13. Rear axle assembly may be stock for make and model of car used. Locked rear ends allowed. Ford or Chrysler one-piece rear ends allowed. Ford 9" allowed. One piece rotors only, weld on caliper mounts OK. Solid steel axles only. All rear end parts must be steel, no aluminum housings, no aluminum spools, no Detroit lockers, no Gold Tracks, no traction control devices of any kind.

14. Drivelines must have two (2) retaining straps, one (1) near the front and one (1) near the back. May be made of chain or metal strap. Drivelines must be painted white. No aluminum drivelines.

15. Steering column must be mounted in stock location. Steering ratio reducers allowed.

16. Complete OEM 4 wheel brakes in good working order required. No turning brakes of any kind allowed. All 4 wheel brakes must work at all times. No dual racing type master cylinders or balance bars allowed. Unaltered OEM working master cylinders must be mounted in OEM location. Unaltered OEM brake pedal assembly and mount only. Must be mounted in OEM location and unaltered. No exceptions.

TIRES AND WHEELS:

1. The Oval Motorsports track tire is available for \$90.
2. Maximum wheel rim width is 7". Steel wheels only. No mag or aluminum wheels allowed. Aftermarket steel wheels are allowed. Any OEM wheels utilized on the right side of car must be reinforced. One (1) bead lock for right rear O.K. Mud plug mandatory.
3. Wheel studs may be replaced with larger studs up to 5/8 inches.

WEIGHT:

1. Minimum weight is 3300 lbs. with driver and passenger except Camaro and Firebird which will be 3400 lbs. with driver and passenger. All ballast weight added to the car must be mounted in a safe and secure manner. All ballast weight must be painted white and must have car number stamped on each weight. All weight must be mounted with a minimum of two (2) 5/8" grade 8 bolts or two (2) weight mounts.
2. Any ballast weight dropped on the racetrack at any time is an automatic disqualification for the remainder of race events.

FUEL SYSTEMS:

1. Gasoline only. No alcohol or boosters of any kind allowed.
2. All fuel lines in the cockpit must be sleeved with steel tubing.
3. Fuel cells are mandatory. Roll over check valves on fuel cell vents required.
4. All fuel cell filler caps will have a safety chain connected to the car.
5. No cool can allowed.

MISCELLANEOUS:

IMPORTANT NOTICE Any part within view is subject to tech at anytime.

1. No radios allowed.
2. Fire extinguisher minimum 2 lbs. dry-chemical must be mounted in driver's compartment. Must be accessible to the driver. Must have quick release mount. Must not be taped or plastic tied in. Additional fire extinguisher must be in pits at all times.
3. Safety helmet must meet Snell 95 testing standards, bear proper identification, and have no signs of

previous damage. No open face helmets allowed. SFI-approved full fire suit required. Fire retardant gloves, shoes and neck brace (or head and neck restraint) required. *Recommended: Fire retardant head sock and underwear.*

4. Neck brace required at all times.

5. Equipment will not be considered "legal" simply because it went through inspection unobserved or because a rule has not been written against it.

6. The Speedway reserves the right to confiscate and hold any parts and/or equipment not conforming to rules.

1. **ENGINE PROTEST PROCEDURES:** Any Oval Motorsports member of the same division can for \$500.00 have a motor torn down to crank shaft for inspection of illegal parts of any starters of the main event within 5 minutes after checkered flag at the tech pad area. Promoter may also protest any engine. \$100.00 to Oval Motorsports, \$400.00 to car owner if found legal. If illegal, \$400.00 will be returned to member contesting car and \$100.00 to Oval Motorsports (\$100.00 to Speedway covers cost required for tech officials to over see procedure). Must have raced the two races in a row prior to requesting an engine tear down. Refusal of tear down will be loss of points and contingencies for that event, two race suspension (car & driver). Car must pass tech inspection before racing privilege are reinstated. \$125.00 inspection fee required to cover tech officials overtime. Second offense – total loss of racing privilege at the speedway.

Engine Claim Rules

1. Top 5 finishers in the main event are subject to having their engine claimed by any driver on the same lap as the event winner.

2. Claim is \$1000 plus exchange of the long block.

3. All motors will be checked to insure that they are legal before the exchange takes place. Any motor found to be illegal will become the property of the speedway.

4. All motors that are claimed will be stamped and must be run by the claimant the following event.

5. Any driver may claim only one motor per season, but the claimed motor may be claimed multiple times.

6. The first refusal of a claim will result in a 21 day suspension, \$500 fine, loss of purse for the night and loss of all accumulated seasonal points to date. Second refusal of claim will result in a 42 day suspension, \$1000 fine and loss of all accumulated seasonal points to date.

7. Drivers wishing to make a claim must drive immediately to the claim area after an event with money and report their intentions to a track official.

8. Driver having their engine claimed has five minutes to decide.

9. The Promoter may make a claim on any engine. \$1000 and no trade. The engine will be put up for bid.